

SIPHONIC ROOF DRAINAGE

REVISED VERSION

By Dr Malcolm Wearing BEng PhD CEng MICE MCIWEM



MGMA Information Sheet No 06

July 2012

Siphonic roof drainage is a controversial subject, usually cited as a great idea or as a terrible idea, depending on the user's past experience. This data sheet sets out to demonstrate how siphonic drainage works, what the advantages and disadvantages are, and will dispel some of the myths which have surrounded the industry in the past.



Siphonic pipework horizontal at high level

INTRODUCTION

Siphonic roof drainage is not a new concept. It was originally developed by the Finnish engineer Ovlai Ebling in the late 1960s and the first commercial installation was in a Swedish turbine factory in 1972. Since its inception, siphonic roof drainage systems have been fitted throughout the world, with the UK market having a number of manufacturers.

The reputation of the UK siphonic industry was greatly damaged in the 1990s by a widespread practice of

installing systems based on 75mm/hr rainfall intensity. This meant that it was inevitable that systems would overflow; but unfortunately it was the siphonic technique that was blamed, and not the low design rainfall levels. There were also a number of companies who have subsequently failed that did not have the technical ability to design siphonic roof drainage correctly and the poor systems installed by them tended to damage the reputation of the whole industry

In June 2004, the Siphonic Roof Drainage Association (SRDA) was formed with the objective of promoting best practice in the siphonic industry (www.siphonic.org). In collaboration with the industry and BSi, the SRDA was instrumental in the introduction of a British Standard for Siphonic Roof Drainage, BS8490:2007.

HOW IT WORKS

All siphonic roof drainage systems work in exactly the same way. Air is excluded by a baffle plate over the outlet hole, which causes the pipes to run full of water. When the pipes are full of water the height difference between the gutter and the discharge point creates negative pressures in the pipe system, which draws water through the system. The greater the drop, the greater the potential energy available, and the greater the overall flow capacity of the outlet. However, if negative pressure becomes too large, cavitation and pipe implosion are risk factors, and so designs must be carried out by a competent person using suitable software.



Vented lid on discharge manhole

In the UK, the practice is for a number of outlets to be joined via small diameter tail pipes into a collector main which runs to a single discharge point. On larger buildings there may be many of these systems. A key factor is to ensure that the tail pipes are able to fill the collector pipe in a reasonable time. In the UK, a two-minute storm is used for roof drainage design, and so if the system takes longer than 60 seconds to fill, it is effectively useless.

As buildings, and thus systems, have got larger in the UK this has become a key element of design.

In many larger systems, drainage is divided into a primary and secondary system. The primary system drains the day to day rainfall but in heavier storms, the secondary system will cut in and remove large volumes of water. Often these secondary systems will discharge onto car parks and other hard surfaces, as underground drainage will often not have the capacity required to accept all the drainage flow. This is a sustainable approach, which reduces the shock load on the drainage system downstream.



Typical primary and secondary siphonic outlets in gutter

One key point is that there are no essential differences in technology between the various manufacturers; all siphonic systems work in the same way.

ADVANTAGES AND DISADVANTAGES

The key advantages of a siphonic system are:

- Drainage pipework is mostly horizontal at high level, freeing space in the building.
- The system is installed later in the construction programme, speeding up the groundworks.
- Underground pipework in the building is virtually eliminated.

Disadvantages are:

- Systems are more susceptible to blockage if poorly maintained.
- Systems can be noisy (only usually an issue if used in the wrong type of building)

SUMMARY

Siphonic roof drainage is the best method of draining large volumes of water from large buildings; however, it is important that regular maintenance is carried out to keep the systems functioning in prime condition. All siphonic systems work in the same way, and the most important factors are how the pipework is sized, to achieve flow balance in system, and the speed with which the system will begin to operate. All siphonic companies should be able to produce calculations showing the system balance, fill time and gutter performance, and it is up to specifiers to make sure that they do.

Dr Malcolm Wearing is managing director of CRM Rainwater Drainage Consultancy Ltd, the UK's principal independent testing organisation for siphonic roof drainage equipment. He sat on both UK and American Society of Mechanical Engineers Standard development groups, as well as being technical consultant to the SRDA and MGMA.

Visit our web site

At www.mgma.co.uk you can contact MGMA members and discover the products and services available. Members are only too pleased to help with any problems you have and can provide design assistance should you need it.

Whilst the information in this data sheet is believed to be correct at the time of going to press, the Metal Gutter Manufacturers Association and its member companies cannot be held responsible for any errors or inaccuracies and, in particular, the specification for any application must be checked with the individual manufacturer concerned for a given installation.

Metal Gutter Manufacturers Association

106 Ruskin Avenue
Rogerstone Newport
South Wales
NP10 0BD

01633 891584
mgmagutters@gmail.com
www.mgma.co.uk

