

## **ADVANTAGES OF PAINTED METAL GUTTERS**

## **INTRODUCTION**

A roof drainage system is an important aspect of the overall roof design and careful selection of materials is essential to avoid the consequences of a failed rainwater system which inevitably result in damage to a building, more than often causing serious internal dampness.

At first glance PVC might seem like an economical solution however, whole life cost comparisons prove that this is not the case. PVC does not have the strength, rigidity, durability or colour fastness of metal rainwater systems.

From the all-important functional perspective, as PVC has a high expansion co-efficient this often causes the material to expand and contract causing the joints to pull apart and leak.

In spite of the latest co-extrusion technology, PVC is still prone to discoloration after a few years. New PVC products such as the substitute cast iron systems are merely over painted with a textured paint finish emulating a cast iron finish; this paint will delaminate after a very short period hence manufacturers only offer 10-year guarantees.

The table overleaf sets out the benefits of metal gutter systems over PVC.

UPVC	METAL
Durability	Durability
PVC gutter systems are attacked by UV causing the material to become brittle hence prone to cracking	Metal systems are UV and corrosion resistant to BS EN 1SO 1461
Aesthetics	Aesthetics
Colour fades after a few years Limited choice of styles, colours and sizes	Excellent colour retention throughout its design life Vast choice of colours, style and sizes
Capacity	Capacity
PVC ranges are generally limited to the domestic market restricting choice and not catering for higher flow capacity requirements	Both proprietary and purpose made systems offer limitless options to suit any building design

Table reproduced courtesy of Akzo Nobel Powder Coatings Limited

## **MGMA DISCLAIMER**

Whilst the information contained in this bulletin is believed to be correct at the time of publication, the Metal Gutter Manufacturers Association Limited and its member companies cannot be held responsible for any errors or inaccuracies and, in particular, the specification for any application must be checked with the individual manufacturer concerned for a given installation.

Information provided by the MGMA or contained within publications and articles which are made available in any form (mechanical, electronic, photocopying or otherwise) cannot be used or cited as a means of ensuring that a material, product, system or assembly is compliant with Building Regulations.

©2018 MGMA 106 Ruskin Avenue, Rogerstone, Newport, Gwent NP10 0BD 01633 891584 mgmagutters@gmail.com www.mgma.co.uk